

ASTM D6641 Compressive Properties of Polymer Matrix Composite Materials using a Combined Loading Compression (CLC) Test Fixture

TEST METHOD SUMMARY

Compression testing of fibre-reinforced composites per ASTM D6641, is used to determine mechanical material property data that are of interest for design specification and quality control.

Uniaxial compression force is applied to a rectangular test specimen held in a combined loading compression (CLC) loading fixture to investigate the stress/strain behavior and critical materials properties including compression modulus, compression strength and compressive failure strain. The CLC loading fixture provides a combined end- and shear-loading of the specimen. The standard addresses general composites that are balanced and symmetric.

The compression test is performed by placing the loading fixture with the test specimen between compression platens of either a servohydraulic or an electromechanical testing machine and subjecting the specimen to controlled compression load until failure. The specimen response can be measured with an extensometer on the edges or strain gauges on both faces of the specimen.

Solutions for ASTM D6641 typically include these types of components:

LOAD FRAME OPTIONS*

The MTS Landmark servohydraulic test systems and MTS Criterion electromechanical universal test systems are ideal for performing accurate and repeatable monotonic testing of polymer matrix composites per ASTM D6641.

The MTS Landmark innovative test frame design exhibits superior stiffness and alignment capabilities. The test system integrates the latest MTS servohydraulic technology including precision-machined columns for consistently tight alignment, fatigue-rated MTS actuators with low friction bearings, smooth-ramping hydraulic service manifolds, and SilentFlo™ hydraulic power units are quiet enough to be located directly in the laboratory.

The compact MTS Criterion test system features high-resolution MTS digital controls, linear motion guides for superior alignment, high-speed, low vibration MTS electromechanical drives, optional Dual Zone test space for maximizing efficiency.

CHAMBER OPTIONS*



MTS Landmark®
Servohydraulic Test Systems



MTS Criterion®
Electromechanical Universal Test Systems

<p>MTS Series 651 Environmental Chambers</p>	<p>MTS Advantage™ Environmental Chamber</p>
<ul style="list-style-type: none"> » Temperature range of -150°C to 540°C (-240°F to 1000°F) » Designed for MTS Landmark systems » Compatible with video extensometers 	<ul style="list-style-type: none"> » Temperature range of -129°C to 315°C (-200°F to 600°F) » Designed for MTS Criterion systems » Compatible with video extensometers

FIXTURE OPTIONS*



ASTM D6641 Combined Loading Compression Fixture

- » Recommended to test in accordance with ASTM D6641
- » Constructed out of high quality stainless steel
- » Static Force Rating: 89 kN (20 kip)
- » Temperature range of -85°C to 122°C (-120°F to 250°F)

SOFTWARE OPTIONS*

ASTM D6641 Compression Properties of Polymer Matrix Composite Materials

To simplify testing to ASTM D6641 MTS has developed a TestSuite™ TW test template that will set-up and run the recommended compression tests. The templates support the use of strain gages or extensometers for strain measurement.

Reports can display all of the required calculations including stress-strain plot, compression modulus, compression strength, compressive failure strain.


MTS consultants are also available to support your composite applications, test method set-up, and data collection and integration requirements.

About MTS TestSuite™ TW

The efficient MTS TestSuite TW software provides the versatility required to address unique and complex testing requirements.

twe TestSuite TW Elite includes all the test definition capacity and flexibility test designers need to create and edit custom test sequences while accommodating the specific runtime needs of lab personnel.


twx TW Express is designed for the test operator and is used to run tests created with TW Elite. This application allows the operator to easily execute even the most complex tests and monitor data or calculated values in runtime views that can be tailored by both test designers and operators.




*NOTE: This technical note is intended to show some of the popular and more common solutions used for this particular application. Most often, additional options are available and necessary to accomplish your more comprehensive test objectives.

APPENDIX - TEST SPECIMEN DETAIL

Procedure A – Untabbed Specimen



Procedure B – Tabbed Specimen



Dimension	Procedure A Untabbed Specimen	Procedure B Tabbed Specimen
Overall length in mm	140	
Thickness	The thickness must be sufficient to preclude Euler column buckling of the specimen, refer to ASTM D6641 standard for details.	
Width in mm	12-13	
Distance between end tabs in mm	–	13
Thickness of end tabs in mm	–	≈1.6



MTS Systems
 14000 Technology Drive
 Eden Prairie, MN 55344-2290 USA
 Telephone: 1-952-937-4000
 Toll Free: 1-800-328-2255
 E-mail: info@mts.com
 www.mts.com

ISO 9001 Certified QMS

MTS, MTS Criterion, SilentFlo, and MTS Landmark are registered trademarks, and MTS TestSuite and MTS Advantage are a trademarks of MTS Systems within the United States. These trademarks may be protected in other countries. RTM No. 211177.

©2021 MTS Systems
 100-361-495 ASTM D6641 • Printed in U.S.A. • 09/21